

100V 15mohm N-channel SGT MOSFET
AKG10N150KL-A

Description:

This device is designed for automotive applications and manufactured in IATF16949 certified facilities. AEC-Q101 Qualified.

Features:



- Low $R_{DS(ON)}$
- RoHS compliant
- Halogen-free
- AEC-Q101 Qualified

Applications:

- Automotive application
- DC-DC Converter

Key Performance Parameters:

Parameter	Value	Unit
V_{DS}	100	V
$R_{DS(ON), max} @ V_{GS} = 10\text{ V}$	15	mΩ
I_D	45	A



Ordering Information:

Ordering Code	Package Type	Marking Code	Form	Packing
AKG10N150KL-A	TO-252	G10N150KL	Tape Reel	See the detail package information

Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Units
V_{DS}	Drain - Source Voltage	100	V
I_D	Drain Current - Continuous ($T_C = 25^\circ\text{C}$) ^(Note 1)	50	A
	Drain Current - Continuous ($T_C = 25^\circ\text{C}$) ^(Note 2)	45	A
	Drain Current - Continuous ($T_C = 100^\circ\text{C}$)	35	A
I_{DM}	Drain Current - Pulsed ^(Note 3)	180	A
V_{GS}	Gate-Source Voltage	± 20	V
E_{AS}	Single Pulsed Avalanche Energy ^(Note 4)	56	mJ
P_D	Power Dissipation ($T_C = 25^\circ\text{C}$)	75	W
T_J, T_{STG}	Operating and Storage Temperature Range	-55 to +175	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Thermal Resistance, Junction - to - Case, Steady-State	2	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction - to - Ambient, Steady State ^(Note 5)	55	$^\circ\text{C/W}$

Notes:

1. The max drain current rating is silicon limited
2. The max drain current rating is package limited
3. Repetitive Rating: Pulse width limited by maximum junction temperature
4. $L = 0.5\text{ mH}$, $V_{DD} = 50\text{ V}$, $I_{AS} = 15\text{ A}$, $R_g = 50\ \Omega$, Starting $T_J = 25\ ^\circ\text{C}$
5. Mount on minimum PCB layout

Electrical Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Static Characteristics						
V _{(BR)DSS}	Drain - Source Breakdown Voltage	V _{GS} = 0 V, I _D = 250 μA	100			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 100 V, V _{GS} = 0 V,			1	μA
I _{GSS}	Gate Leakage Current	V _{GS} = ± 20 V, V _{DS} = 0 V			±100	nA
V _{GS(th)}	Gate Threshold voltage	V _{DS} = V _{GS} , I _D = 250 μA	1	2	3	V
R _{DS(ON)}	Drain - Source on - state resistance	V _{GS} = 10 V, I _D = 20 A		11.5	15	mΩ
		V _{GS} = 4.5 V, I _D = 20 A		16	22	
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} = 50 V, V _{GS} = 0 V, f = 1 MHz		1355		pF
C _{oss}	Output Capacitance			345		pF
C _{rss}	Reverse Transfer Capacitance			25		pF
R _g	Gate Resistance	f = 1 MHz		1		Ω
Switching Characteristics						
t _{d(on)}	Turn On Delay Time	V _{DD} = 50 V , R _L = 2.5 Ω, V _{GS} = 10 V, R _G = 6.8 Ω		9		ns
t _r	Rise Time			26		ns
t _{d(off)}	Turn Off Delay Time			27		ns
t _f	Fall Time			41		ns
Q _g	Total Gate Charge	V _{DD} = 50 V , I _D = 20 A, V _{GS} = 10 V		25		nC
Q _{gs}	Gate - Source Charge			4		nC
Q _{gd}	Gate - Drain Charge			8		nC
Drain - Source Diode Characteristics and Maximum Ratings						
I _S	Maximum Continuous Body - Diode Forward Current				45	A
I _{SM}	Maximum Pulsed Body - Diode Forward Current				180	A
V _{SD}	Diode Forward Voltage	V _{GS} = 0 V, I _S = 1 A		0.73		V
t _{rr}	Reverse recovery time	V _{DD} = 50 V, I _D = 20 A, di/dt = 100 A/μs		48		ns
Q _{rr}	Reverse recovery charge			58		nC
I _{rrm}	Peak Reverse Recovery Current			2.2		A

Electrical Characteristics Diagrams




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: Breakdown Voltage vs. Junction Temperature










Figure 6: Threshold Voltage vs. Junction Temperature






Figure 13: Normalized Maximum Transient Thermal Impedance






Figure 14: Maximum Forward Biased Safe Operating Area

Test Circuit and Waveform


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



Revision History

Revision	Released	Remark
Rev.1.0	2023	Initial Release

Disclaimer

The information given in this document describes the independent performance of the product, but similar performance is not guaranteed under other working conditions, and cannot be guaranteed when installed with other products or equipment. To achieve the required performance of the product in actual scenarios, the customer should conduct a complete application test to assess the functionality of the product.

Alkaidsemi assumes no responsibility for equipment failures result from using products at values that exceed the ratings, operating conditions, or other parameters listed in the product specifications.

The product described in this specification is not applicable for aerospace or other applications which requires high reliability. Customers using or selling these products for use in medical, life-saving, or life-sustaining applications do so at their own risk and agree to fully indemnify.

Due to product or technical improvements, the information described or contained herein may be changed without prior notice.