

70V 5.9mohm N-channel SGT MOSFET
AKG7N059GM

Description:

This N channel SGT MOSFET has been designed to low on-state resistance and maintain superior switching performance, especial for high efficiency power management applications.

Features:



- Low $R_{DS(ON)}$
- RoHS compliant (Note 1)
- Halogen-free (Note 1)

Applications:

- Battery Management System
- Motor Drivers
- DC-DC Converter

Key Performance Parameters:

Parameter	Value	Unit
V_{DS}	70	V
$R_{DS(ON), max} @V_{GS} = 10V$	5.9	mΩ
I_D	60	A



Ordering Information:

Ordering Code	Package Type	Marking Code	Form	Packing
AKG7N059GM	PDFN5X6	G7N059GM	Tape Reel	5000PCS

Notes:

1. Contact ALKAIDSEMI sales for detail information



Maximum Ratings (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Value	Units
V _{DS}	Drain-Source Voltage	70	V
I _D	Drain Current - Continuous (T _C = 25°C) ^(Note 1)	81	A
	Drain Current - Continuous (T _C = 25°C) ^(Note 2)	60	A
	Drain Current - Continuous (T _C = 100°C)	51	A
I _{DM}	Drain Current - Pulsed ^(Note 3)	240	A
V _{GS}	Gate-Source Voltage	± 20	V
E _{AS}	Single Pulsed Avalanche Energy ^(Note 4)	168	mJ
P _D	Power Dissipation (T _C = 25°C)	65	W
T _J , T _{STG}	Operating and Storage Temperature Range	-55 to +150	°C

Thermal Characteristics

Symbol	Parameter	Value	Units
R _{θJC}	Thermal Resistance, Junction-to-Case, Steady-State	1.9	°C/W
R _{θJA}	Thermal Resistance, Junction-to-Ambient, Steady State ^(Note 5)	45	°C/W







Notes:







- 1. The max drain current rating is silicon limited
- 2. The max drain current rating is package limited
- 3. Repetitive Rating: Pulse width limited by maximum junction temperature
- 4. L = 0.5 mH, V_{DD} = 35 V, I_{AS} = 25.5 A, R_G = 50 Ω, Starting T_J = 25 °C
- 5. Mount on minimum PCB layout



Electrical Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0 V, I _D = 250 μA	70			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 70 V, V _{GS} = 0 V,			1	μA
I _{GSS}	Gate Leakage Current	V _{GS} = ± 20 V, V _{DS} = 0 V			±100	nA
V _{GS(TH)}	Gate Threshold voltage	V _{DS} = V _{GS} , I _D = 250 μA	2	3	4	V
R _{DS(ON)}	Drain-Source on-state resistance	V _{GS} = 10, I _D = 40 A		5.1	5.9	mΩ
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{DS} =35 V, V _{GS} = 0 V, F = 1 MHz		2056		pF
C _{OSS}	Output Capacitance			716		pF
C _{RSS}	Reverse Transfer Capacitance			49.5		pF
R _G	Gate Resistance	F = 1 MHz		1.7		Ω
Switching Characteristics						
T _{D(ON)}	Turn On Delay Time	V _{DD} = 35 V , R _L = 0.9 Ω, V _{GS} = 10 V, R _G = 2.7 Ω		14		nS
T _R	Rise Time			48		nS
T _{D(OFF)}	Turn Off Delay Time			28.5		nS
T _F	Fall Time			12		nS
Q _G	Total Gate Charge	V _{DD} = 35 V , I _D = 40 A, V _{GS} = 10 V		37		nC
Q _{GS}	Gate-Source Charge			8.5		nC
Q _{GD}	Gate-Drain Charge			13		nC
Drain-Source Diode Characteristics and Maximum Ratings						
I _S	Maximum Continuous Body-Diode Forward Current				60	A
I _{SM}	Maximum Pulsed Body-Diode Forward Current ^(NOTE 1)				240	A
V _{SD}	Diode Forward Voltage	V _{GS} = 0 V, I _S = 40 A		0.9		V
T _{RR}	Reverse recovery time	V _{DD} = 35 V, I _D = 40 A, di/dt = 100 A/μS		40		nS
Q _{RR}	Reverse recovery charge			28		nC
I _{RRM}	Peak Reverse Recovery Current			1.4		A

Electrical Characteristics Diagrams











Test Circuit and Waveform



Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms





Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms




Package Outlines




SYMBOL	MIN	NOM	MAX
A	0.90	1.00	1.10
b	0.20	0.30	0.40
c	0.21	0.25	0.34
D	—	—	5.10
D1	4.80	4.90	5.00
D2	3.91	4.01	4.11
e	1.27 BSC		
E	5.90	6.00	6.10
E1	5.65	5.75	5.85
E2	3.375	3.475	3.575
H	0.55	0.65	0.75
h	—	—	0.10
K	1.20	—	—
L	0.55	0.65	0.75
L1	0.05	0.15	0.25
L2	—	—	0.12
Θ	8°	10°	12°
P	1.00	1.10	1.20

Unit in mm

Marking Information



Note:
G7N059GM = Product Name Code
XXXX = Date code
YYY
Contact ALKAIDSEMI sales for detail information



Revision History

Revision	Release Date	Remark
Rev.1.0	2023/3/8	Initial Release

Disclaimer

The information given in this document describes the independent performance of the product, but similar performance is not guaranteed under other working conditions, and cannot be guaranteed when installed with other products or equipment. To achieve the required performance of the product in actual scenarios, the customer should conduct a complete application test to assess the functionality of the product.

Alkaidsemi assumes no responsibility for equipment failures result from using products at values that exceed the ratings, operating conditions, or other parameters listed in the product specifications.

The product described in this specification is not applicable for aerospace or other applications which requires high reliability. Customers using or selling these products for use in medical, life-saving, or life-sustaining applications do so at their own risk and agree to fully indemnify.

Due to product or technical improvements, the information described or contained herein may be changed without prior notice.